PASSENGER AND COMMERCIAL
AIR JACKS

selson
air jacks & torque multipliers



Selson Air Jacks are a unique design that uses compressed air to raise and lower motor vehicles quickly and easily. Their safety, reliability and speed make Selson Air Jacks the ideal choice for underbody servicing, wheel alignment, tyre replacement services and body repair work.

FAST AND FRIENDLY

Two push button valves make Selson Air Jacks quick and easy to operate. Press green to raise and press red to lower. Their speed of operation over conventional jacks will significantly reduce the time required to lift a vehicle. And because they are light weight relative to their capacity, they are portable.

DESIGNED FOR STABILITY

Inside the Selson Air Jack there is a unique internal telescopic stabilising column., which provides stability to the jack during elevation but still allows some lateral movement. This enables the head cap of the jack to follow the arc of the vehicle being elevated, and when combined with the wide base, gives maximum stability on hard or soft surfaces.

EASY-CARE LONG LIFE

Very few moving parts mean maintenance costs associated with Selson Air Jacks are kept to an absolute minimum. The air springs are made of a 2-ply neoprene rubber, that is oil and ozone resistant and will not easily perish or crack.

ACCESSORIES

Body Lift Headcap

Used to jack passenger vehicles under pinch-weld seam of sill section.

Part No. 8-007

Polyurethane Headcap

To suit models for passenger and light commercial vehicles.

Headcap 8-008
50mm 2” ext. 8-050
100mm 4” ext. 8-100

24 MONTH WARRANTY

The Selson Air Jacks range also carries our standard 24 months warranty against faulty workmanship and materials, and is backed by a comprehensive service and replacement parts network

Important! The Selson Air Jack is a lifting device only, vehicle support stands are recommended for holding loads in position

Copyright 2026 Selson Pty Ltd (c)

sales@selson.com www.selson.com @selsonuk @selsonairjacks

HANDHELD MODEL | ROLL AROUND MODEL

HBNXLO



2 BELLOWS

HXLO



HBN3



3 BELLOWS

H3



PRODUCT INFORMATION

Model	Lift Capicity		Minimum Height		Maximum Height		Working Pressure		Shipping Weight	
	Kg	Tons	mm	inches	mm	inches	kPa	psi	kg	lbs
HBNXLO	2500	2.5	130	5.1	340	13.4	690	100	13	28.6
HBN3	2500	2.5	155	6.1	465	18.3	690	100	16	35.3
HXLO	2500	2.5	130	5.1	340	13.4	690	100	14	30.9
H3	2500	2.5	155	6.1	465	18.3	690	100	19	41.9

Copyright 2026 Selson Pty Ltd (c)

CONTACT US

sales@selson.com

www.selson.com

Unit 5, Arcot Court, Cramlington,
Northumberland, NE23 1BB